




NTN Bearing Rolamentos do Brasil Ltda.



skf SAW 23526 TLC SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAW 23526 TLC

SAW 23526 TLC Bearing 2D drawings and 3D CAD models

d_a	112.713 mm
D_a	230 mm
C_a	89.789 mm
A_1	133.35 mm
A_2	193.675 mm
S	4.763 mm
b_a	65.881 mm
H	295.275 mm
H_1	152.4 mm
H_2	60.325 mm
J min.	371.475 mm
J max.	406.4 mm
J_1	82.55 mm
L	466.725 mm
N_1	25.4 mm
R_1	79.375 mm
R_2	36.513 mm
R_G	1/2 NPT
P_G	1/4 NPT
h	60.325 mm
Housing	SAW 526
Stabilizing ring	SR-26-0
Labyrinth ring	2 x LOR 117
PosiTrac Plus contact element	2 x B10724-117
End plug (suffix Y)	EPR 15



NTN Bearing Rolamentos do Brasil Ltda.

Max. speed for PosiTrac Plus seal	1300 r/min
P _{60°}	189 kN
P _{90°}	113 kN
P _{120°}	73.8 kN
P _{150°}	68.1 kN
P _{180°}	84.5 kN
P _a	31.2 kN
Mass pillow block	68 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	400 N · m
Cap bolt, SAE grade	5
Eye bolt	3/8-16 UNC
Appropriate attachment bolt size G	0.875 in
Initial grease fill	382.73 g