




NTN Bearing Rolamentos do Brasil Ltda.



skf SAFS 22528 x 4.7/8 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAFS 22528 x 4.7/8 T

SAFS 22528 x 4.7/8 T Bearing 2D drawings and 3D CAD models

d_a	123.825 mm
D_a	250 mm
C_a	77.8 mm
A_1	149.225 mm
A_2	260.35 mm
S	4.763 mm
b_a	61.119 mm
H	298.45 mm
H_1	152.4 mm
H_2	60.325 mm
J min.	406.4 mm
J max.	434.975 mm
J_1	85.725 mm
L	511.175 mm
N_1	28.575 mm
R_1	87.313 mm
R_2	38.1 mm
R_G	3/4 NPT
P_G	1/4 NPT
h	51.594 mm
Housing	SAFS 528
Stabilizing ring	SR-28-0
Taconite seal	TER 121
End plug (suffix Y)	EPR 27
Max. speed for Taconite seal	625 r/min



NTN Bearing Rolamentos do Brasil Ltda.

P _{60°}	301 kN
P _{90°}	180 kN
P _{120°}	116 kN
P _{150°}	105 kN
P _{180°}	127 kN
P _a	28.5 kN
Mass pillow block	92.5 kg
Cap bolt	7/8-9 UNC
Cap bolt recommended tightening torque	813.5 N · m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	481.95 g