




NTN Bearing Rolamentos do Brasil Ltda.



skf SAF 23026 KATLC x 4.7/16 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 23026 KATLC x 4.7/16

SAF 23026 KATLC x 4.7/16 Bearing 2D drawings and 3D CAD models

d_a	112.713 mm
D_a	200 mm
C_a	62.789 mm
A_1	120.65 mm
A_2	165.1 mm
b_a	51.594 mm
H	239.713 mm
H_1	125.425 mm
H_2	50.8 mm
J min.	320.675 mm
J max.	368.3 mm
J_1	69.85 mm
L	419.1 mm
N_1	22.225 mm
R_1	67.945 mm
R_2	31.75 mm
R_G	3/8 NPT
P_G	1/4 NPT
h	42.862 mm
Housing	SAF 026 KA
Bearing	23026 CCK/W33
Adapter sleeve assembly	SNW 3026x4.7/16
Stabilizing ring	2 x 38151-26
Labyrinth ring	2 x LOR 117
PosiTrac Plus contact element	2 x B10724-117



NTN Bearing Rolamentos do Brasil Ltda.

End plug (suffix Y)	EPR 15
Max. speed for PosiTrac Plus seal	1300 r/min
P _{60°}	149 kN
P _{90°}	89 kN
P _{120°}	55.6 kN
P _{150°}	50.7 kN
P _{180°}	60.9 kN
P _a	20.2 kN
Mass pillow block	32.2 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N · m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	232.47 g