




NTN Bearing Rolamentos do Brasil Ltda.



skf SAF 22526 x 4.1/2 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 22526 x 4.1/2 T

SAF 22526 x 4.1/2 T Bearing 2D drawings and 3D CAD models

d_a	114.3 mm
D_a	230 mm
C_a	73.787 mm
A_1	133.35 mm
A_2	269.875 mm
S	4.763 mm
b_a	57.944 mm
H	295.275 mm
H_1	152.4 mm
H_2	60.325 mm
J min.	371.475 mm
J max.	406.4 mm
J_1	82.55 mm
L	466.725 mm
N_1	25.4 mm
R_1	79.375 mm
R_2	36.513 mm
R_G	1/2 NPT
P_G	1/4 NPT
h	59.531 mm
Housing	SAF 526
Stabilizing ring	SR-26-0
Taconite seal	TER 118
End plug (suffix Y)	EPR 15
Max. speed for Taconite seal	700 r/min



NTN Bearing Rolamentos do Brasil Ltda.

P _{60°}	189 kN
P _{90°}	113 kN
P _{120°}	73.8 kN
P _{150°}	68.1 kN
P _{180°}	84.5 kN
P _a	24.9 kN
Mass pillow block	64.5 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	400 N · m
Cap bolt, SAE grade	5
Eye bolt	3/8-16 UNC
Appropriate attachment bolt size G	0.875 in
Initial grease fill	382.73 g