




# NTN Bearing Rolamentos do Brasil Ltda.



skf SAF 22615 x 2.1/2 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 22615 x 2.1/2 T

SAF 22615 x 2.1/2 T Bearing 2D drawings and 3D CAD models

$d_a$	63.5 mm
$D_a$	160 mm
$C_a$	64.795 mm
$A_1$	98.425 mm
$A_2$	223.838 mm
S	4.763 mm
$b_a$	44.45 mm
H	192.088 mm
$H_1$	101.6 mm
$H_2$	41.275 mm
J min.	263.525 mm
J max.	295.275 mm
L	349.25 mm
$N_1$	22.225 mm
$R_1$	60.325 mm
$R_2$	27.94 mm
$R_G$	3/8 NPT
$P_G$	1/8 NPT
h	40.481 mm
Housing	SAF 615
Stabilizing ring	SR-18-15
Taconite seal	TER 38
End plug (suffix Y)	EPR 7
Max. speed for Taconite seal	1250 r/min
$P_{60^\circ}$	121 kN



## NTN Bearing Rolamentos do Brasil Ltda.

P <sub>90°</sub>	72.5 kN
P <sub>120°</sub>	45.4 kN
P <sub>150°</sub>	40.5 kN
P <sub>180°</sub>	49.8 kN
P <sub>a</sub>	12.5 kN
Mass pillow block	24.3 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	141.75 g