




# NTN Bearing Rolamentos do Brasil Ltda.



skf SAFS 23028 KAT x 5 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAFS 23028 KAT x 5

SAFS 23028 KAT x 5 Bearing 2D drawings and 3D CAD models

$d_a$	127 mm
$D_a$	210 mm
$C_a$	72.619 mm
$A_1$	120.65 mm
$A_2$	250.825 mm
$b_a$	53.975 mm
H	257.175 mm
$H_1$	133.35 mm
$H_2$	53.975 mm
J min.	336.55 mm
J max.	368.3 mm
$J_1$	69.85 mm
L	419.1 mm
$N_1$	22.225 mm
$R_1$	79.375 mm
$R_2$	30.163 mm
$R_G$	1/2 NPT
$P_G$	1/4 NPT
h	46.038 mm
Housing	SAFS 028 KA
Bearing	23028 CCK/W33
Adapter sleeve assembly	SNW 3028x5
Stabilizing ring	2 x 36053-50
Taconite seal	TER 123
End plug (suffix Y)	EPR 27



## NTN Bearing Rolamentos do Brasil Ltda.

Max. speed for Taconite seal	625 r/min
P <sub>60°</sub>	249 kN
P <sub>90°</sub>	149 kN
P <sub>120°</sub>	94.3 kN
P <sub>150°</sub>	87.2 kN
P <sub>180°</sub>	107 kN
P <sub>a</sub>	22.2 kN
Mass pillow block	60.3 kg
Cap bolt	5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	0.75 in
Initial grease fill	379.89 g