




NTN Bearing Rolamentos do Brasil Ltda.



skf SAF 22626 x 4.5/16 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 22626 x 4.5/16 T

SAF 22626 x 4.5/16 T Bearing 2D drawings and 3D CAD models

d_a	109.537 mm
D_a	279.999 mm
C_a	102.794 mm
A_1	158.75 mm
A_2	288.925 mm
S	4.763 mm
b_a	72.231 mm
H	336.55 mm
H_1	169.875 mm
H_2	66.675 mm
J min.	441.325 mm
J max.	488.95 mm
J_1	95.25 mm
L	558.8 mm
N_1	28.575 mm
R_1	104.775 mm
R_2	33.337 mm
R_G	3/4 NPT
P_G	1/4 NPT
h	61.913 mm
Housing	SAF 626
Stabilizing ring	SR-0-26
Taconite seal	TER 115
End plug (suffix Y)	EPR 15
Max. speed for Taconite seal	700 r/min



NTN Bearing Rolamentos do Brasil Ltda.

P_{60°	226 kN
P_{90°	136 kN
P_{120°	85.9 kN
P_{150°	78.3 kN
P_{180°	94.3 kN
P_a	36.3 kN
Mass pillow block	108 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N · m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	793.8 g