



NTN Bearing Rolamentos do Brasil Ltda.



skf SAF 22515 x 2.3/8 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 22515 x 2.3/8 T

SAF 22515 x 2.3/8 T Bearing 2D drawings and 3D CAD models

d_a	60.325 mm
D_a	130 mm
C_a	37.008 mm
A_1	79.375 mm
A_2	193.675 mm
S	3.175 mm
b_a	32.544 mm
H	157.559 mm
H_1	82.55 mm
H_2	28.575 mm
J min.	219.075 mm
J max.	244.475 mm
L	285.75 mm
N_1	19.05 mm
R_1	46.038 mm
R_2	21.431 mm
R_G	1/4 NPT
P_G	1/8 NPT
h	28.575 mm
Housing	SAF 515
Stabilizing ring	SR-15-0
Taconite seal	TER 36
End plug (suffix Y)	EPR 7
Max. speed for Taconite seal	1250 r/min
P_{60°	75.6 kN



NTN Bearing Rolamentos do Brasil Ltda.

P_{90°	45.4 kN
P_{120°	28 kN
P_{150°	25.4 kN
P_{180°	30.2 kN
P_a	6.94 kN
Mass pillow block	12.7 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	81.3 N · m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.625 in
Initial grease fill	68.04 g