



# NTN Bearing Rolamentos do Brasil Ltda.



skf SAFS 23026 KAT x 4.3/8 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAFS 23026 KAT x 4.3/8

SAFS 23026 KAT x 4.3/8 Bearing 2D drawings and 3D CAD models

$d_a$	111.125 mm
$D_a$	200 mm
$C_a$	62.789 mm
$A_1$	120.65 mm
$A_2$	231.775 mm
$b_a$	51.594 mm
H	244.475 mm
$H_1$	125.425 mm
$H_2$	52.388 mm
J min.	320.675 mm
J max.	368.3 mm
$J_1$	69.85 mm
L	419.1 mm
$N_1$	24.209 mm
$R_1$	73.025 mm
$R_2$	31.75 mm
$R_G$	3/8 NPT
$P_G$	1/4 NPT
h	40.922 mm
Housing	SAFS 026 KA
Stabilizing ring	2 x 38151-26
Taconite seal	TER 116
End plug (suffix Y)	EPR 15
Max. speed for Taconite seal	700 r/min
$P_{60^\circ}$	178 kN



## NTN Bearing Rolamentos do Brasil Ltda.

P <sub>90°</sub>	107 kN
P <sub>120°</sub>	66.7 kN
P <sub>150°</sub>	59.6 kN
P <sub>180°</sub>	72.5 kN
P <sub>a</sub>	20.2 kN
Mass pillow block	50.8 kg
Cap bolt	5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	0.75 in
Initial grease fill	232.47 g