



NTN Bearing Rolamentos do Brasil Ltda.



skf SALKB 16 F Spherical plain bearings and rod ends with a male thread

Bearing No. SALKB 16 F

SALKB 16 F Bearing 2D drawings and 3D CAD models

Category	Spherical Plain Bearings - Rod Ends
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.2
EAN	7316577001931
Product Group	B04286
Stud Profile	Male
Mounting Thread	M16 X 2
Thread Direction	Left Hand
Rolling Element	Spherical Plain
Material - Outer Member	Steel
Material - Ball	Steel
Material - Liner	Plastic Teflon
Relubricatable	No
Enclosure	Open
Other Features	2 Piece Zinc Plated Outer Self Lubricating Maintenance Free
Long Description	16MM Bore; 15MM House Width; Male Stud Profile; M16 X 2; Left Hand Thread Direction; Spherical Plain Bearing; Steel Outer Member; Steel Ball; Plastic
Inch - Metric	Metric
Category	Plain Bearing Spherical Rod



NTN Bearing Rolamentos do Brasil Ltda.

	Ends
UNSPSC	31171508
Harmonized Tariff Code	8483.30.80.55
Noun	Bearing
Keyword 3	Rod End
Keyword String	Plain Spherical Rod End
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	SALKB 16 F
Weight / LBS	0.441
Housing Width	0.591 Inch 15 Millimeter
Ball Width	0.827 Inch 21 Millimeter
d	0.63 Inch 16 Millimeter
bore diameter:	16 mm
ball material:	Steel
misalignment angle:	15 °
race material:	PTFE Composite
shank thread length:	37 mm
radial static load capacity:	34.5 kN
rod end type:	Male Threaded
operating temperature range:	-40 to +75 ° F
shank thread size:	M16
head diameter:	43 mm
thread direction:	Left Hand
head width:	15 mm
grade:	Commercial/Industrial
ball width:	21 mm
lubrication type:	Maintenance Free/Self-Lubricating
length to ball center:	66 mm
housing material:	Zinc-Plated Steel
standards met:	ISO 12240-4:1998, ISO 965-1:1998



NTN Bearing Rolamentos do Brasil Ltda.

d	16 mm
d ₂ max.	43 mm
B	21 mm
G	M 16
C ₁ max.	15.5 mm
h	66 mm
	15 °
d _k	28.5 mm
l ₁ min.	37 mm
l ₂ max.	89 mm
l ₇ min.	21 mm
r ₁ min.	0.3 mm
Basic dynamic load rating C	21.4 kN
Basic static load rating C ₀	34.5 kN
Specific dynamic load factor K	50 N/mm ²
Material constant K _M	530
Mass rod end	0.2 kg