



NTN Bearing Rolamentos do Brasil Ltda.



skf SALKAC 16 M Spherical plain bearings and rod ends with a male thread

Bearing No. SALKAC 16 M

SALKAC 16 M Bearing 2D drawings and 3D CAD models

Category	Spherical Plain Bearings - Rod Ends
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.19
EAN	7316577001924
Product Group	B04286
Stud Profile	Male
Mounting Thread	M16 X 2
Thread Direction	Left Hand
Rolling Element	Spherical Plain
Material - Outer Member	Steel
Material - Ball	Steel
Material - Liner	Bronze
Relubricatable	Yes
Enclosure	Open
Other Features	3 Piece Zinc Plated Outer
Long Description	16MM Bore; 15MM House Width; Male Stud Profile; M16 X 2; Left Hand Thread Direction; Spherical Plain Bearing; Steel Outer Member; Steel Ball; Bronze L
Inch - Metric	Metric
Category	Plain Bearing Spherical Rod Ends



NTN Bearing Rolamentos do Brasil Ltda.

UNSPSC	31171508
Harmonized Tariff Code	8483.30.80.55
Noun	Bearing
Keyword 3	Rod End
Keyword String	Plain Spherical Rod End
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	SALKAC 16 M
Weight / LBS	0.419
Housing Width	0.591 Inch 15 Millimeter
Ball Width	0.827 Inch 21 Millimeter
d	0.63 Inch 16 Millimeter
bore diameter:	16 mm
ball material:	Steel
misalignment angle:	15 °
race material:	Bronze
shank thread length:	37 mm
radial static load capacity:	23.2 kN
rod end type:	Male Threaded
operating temperature range:	-30 to +180 ° F
shank thread size:	M16
head diameter:	43 mm
thread direction:	Left Hand
head width:	15 mm
grade:	Commercial/Industrial
ball width:	21 mm
lubrication type:	With Lubrication Fitting
length to ball center:	66 mm
housing material:	Zinc-Plated Steel
standards met:	ISO 12240-4:1998, DIN 3405:1986
d	16 mm
d ₂ max.	43 mm



NTN Bearing Rolamentos do Brasil Ltda.

B	21 mm
G	M 16
C ₁ max.	15.5 mm
h	66 mm
	15 °
d _k	28.5 mm
l ₁ min.	37 mm
l ₂ max.	89 mm
r ₁ min.	0.3 mm
Basic dynamic load rating C	21.6 kN
Basic static load rating C ₀	23.2 kN
Specific dynamic load factor K	50 N/mm ²
Material constant K _M	330
Mass rod end	0.19 kg